



FL 155H-G Dual grade laser for beginners







TECHNICAL DATA	FL 155H-G	FEATURES	SUPPLIED WITH FL 155H-G + FR 45
Self-levelling range Laser class Accuracy Working range with receiver (Ø) with FR 45 with FR 77-MM Horizontal slope setting X-Axis	±6° 2 ± 0.5mm / 10m 1200 m 600 m ± 10.000%	Horizontal Dual Grade Laser Digital grade adjustment Monitored grade Automatic TILT function VWS function combined with TILT function Illuminated display Zonal control (masking)	ART-NO. 213145 Receiver FR 45 with clamp 2-Way RF Remote control Li-lon battery Intelligent battery charger Battery case for alkaline batteries Carrying case
Y-Axis X and Y-Axis Rotating speed Operating time	$\pm 10.000\%$ $\Sigma \pm 14\%$ 600 rpm 30 h	Zonal control (electronic beam screen) Remote control screen Li-lon battery technology	SUPPLIED WITH FL 155H-G + FR 77-MM ART-NO. 213177
Power supply RF Remote control range Temperature range Dust / water protection Weight (instrument only)	Li-lon 80 m -20°C to +50°C IP 65 2.2 kg	Battery charger includes adapter for in-car charging	 Receiver FR 77-MM with clamp 2-Way RF Remote control Li-Ion battery Intelligent battery charger Battery case for alkaline batteries Carrying case